



**5411 Seymour Hwy Wichita Falls, TX 76301**

**Tel: 940-767-7694 Fax: 940-687-0751**

**WWW.NITROUSEXPRESS.COM**

**Caution – EXTREME DANGER – Caution**

**Do not use or mix any other manufacturer's products with any Nitrous Express products.**

**Do not use or mix any Nitrous Express products with any other manufacturer's products.**

**THESE INSTRUCTIONS APPLY TO NITROUS EXPRESS PRODUCTS ONLY!**

**FOR SANCTIONED RACE USE ONLY - NOT FOR SALE OR USE IN CALIFORNIA**

### **WIDE OPEN THROTTLE (WOT) SWITCH-PART # 15524**

This WOT micro-switch is designed to work with the universal mounting bracket. Its maximum capacity is 10 AMPS and should only be used to activate low amp draw accessories or in conjunction with a relay.

1. Assemble the micro-switch on the mounting bracket using the supplied 3/4" 4-40 bolts and nuts. The switch can be mounted in several different configurations, select the position you require and tighten the bolts. Do not over-tighten; the plastic micro switch can be damaged.
2. The mounting bracket is made of easily bendable material and may be formed to any configuration that will allow it to place the WOT switch in the proper location.
3. The activation arm on the micro-switch is extra-long. This allows you to twist, bend, or cut it to aid in the ease of installation.